

## PADO 900




<b>Part number</b>	304089
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	20 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK05 0.70J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	1974 lm
<b>Luminaire lumen output:</b>	1080 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°



### Description

- Post mounted outdoor luminaire for general lighting, including:
- Polyester powder coated die-cast aluminium housing
  - Internally frosted glass diffuser
  - Silicone gasket
  - External electrical connection with sealed plug-socket QUICK, complete with cable
  - Stainless steel locking screws
  - Painted extruded aluminium post (h 900 mm) with base plate for the PADO 900 model
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

