

PADO




Part number	304095
Lampholder:	LED
Light Source:	LED
Wattage:	20 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	2061 lm
Luminaire lumen output:	1160 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°




Description

- Post mounted outdoor luminaire for general lighting, including:
- Polyester powder coated die-cast aluminium housing
 - Adapter for posts \varnothing 42-45 mm made of polyester powder-coated die-cast aluminium
 - Internally frosted glass diffuser
 - Silicone gasket
 - External electrical connection with sealed plug-socket QUICK, complete with cable
 - Stainless steel locking screws
 - Powder polyester painting process optimized against UV rays in 13 different steps
 - PADO versions are suitable for installation on existing poles \varnothing 60 mm
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

PADO



310481
Pole top adaptor Ø 45 mm PADO