

TERMINAL BLOCKS FOR P.C.B. RISING CLAMP

MORSETTI PER C.S. CARRELLO

BLOCS DE JONCTION C.I. ÉTRIER REMONTANT


PRINTKLEMMEN LIFTPRINTZIP

| | |
|-------------------------------------------|------------------------|
| Pitch Passo | mm |
| Rated Voltage Tensione nominale | V |
| Rated Current Intensità nominale | A |
| Types of cables Type of conductor | mm ² AWG |
| Nominal cross section Sezione nominale | mm ² |
| Stripping length Lunghezza spelatura | mm |
| Torque Coppia di torsione | Nm |
| Temperature Temperatura | °C |
| Housing Corpo isolante | |
| Captive Screw Vite Imperdibile | |

| | |
|-----|-----------------------|
| IMQ | EN 60998 |
| VDE | EN 60998 |
| cUL | UL 1059 + C22.2 n°158 |

| | |
|-----------------------------------------|----|
| Poles Poli | X |
| Colours Colori | Y |
| Other information Altre informazioni | P. |

| | | | |
|------------------|--------------------|------------------|---------------------|
| MRT5 P10 / X | DP | Y | N... |
| Type Tipo | Pitch Passo | Poles Poli | Version Versione |
| Colors Colori | Markings Marche | Colors Colori | Markings Marche |



* SQ Version = Horizontal version

MRT5..DP

Interlocking modules - Modulo componibile
Elementi modulari - Zusammensteckbare Blöcke

Poles - Poli - Póles - Polzahl 1/2




| |
|------------|
| 10 - 10,16 |
| 630 |
| 24 |

| | | |
|--------------------|----------------------|----------------------|
| 0,2 ÷ 4 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 |
| 6 | | |
| 0,5 | / | 5 |
| 110 | | |
| PA - UL 94 V0 | | |
| M3 | | |
| 0,6 x 3,5 | | |

| | | |
|-----|----|----------------------|
| V | A | mm ² /AWG |
| 750 | 24 | 0,5 ÷ 2,5 |
| 300 | 16 | 24 ÷ 12 |

| |
|-------------------------------------|
| min 2 - max ... |
| VE / on demand GR GR1 NE AR BL RO G |
| D/A1 |



MRT15

Single block - Blocco unico
Monoblocc - Einzelblock

Poles - Poli - Póles - Polzahl 2/24





| |
|----------|
| 5 - 5,08 |
| 320 |
| 24 |

| | | |
|--------------------|----------------------|----------------------|
| 0,2 ÷ 4 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 |
| 6 | | |
| 0,5 | / | 5 |
| 110 | | |
| PA - UL 94 V0 | | |
| M3 | | |
| 0,6 x 3,5 | | |

| | | |
|-----|----|----------------------|
| V | A | mm ² /AWG |
| 450 | 24 | 0,5 ÷ 2,5 |
| 300 | 16 | 30 ÷ 12 |

| |
|-------------------------------------|
| min 2 - max 24 |
| VE / on demand GR GR1 NE AR BL RO G |
| D/A1 |



MRT15..DP

Single block - Blocco unico
Monoblocc - Einzelblock

Poles - Poli - Póles - Polzahl 2/24




| |
|----------|
| 5 - 5,08 |
| 320 |
| 24 |

| | | |
|--------------------|----------------------|----------------------|
| 0,2 ÷ 4 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 |
| 6 | | |
| 0,5 | / | 5 |
| 110 | | |
| PA - UL 94 V0 | | |
| M3 | | |
| 0,6 x 3,5 | | |

| | | |
|-----|----|----------------------|
| V | A | mm ² /AWG |
| 450 | 24 | 0,5 ÷ 2,5 |
| 300 | 16 | 30 ÷ 12 |

| |
|-------------------------------------|
| min 2 - max 24 |
| VE / on demand GR GR1 NE AR BL RO G |
| D/A1 |



MRT15

Single block - Blocco unico
Monoblocc - Einzelblock

Poles - Poli - Póles - Polzahl 2/12





| |
|------------|
| 10 - 10,16 |
| 630 |
| 24 |

| | | |
|--------------------|----------------------|----------------------|
| 0,2 ÷ 4 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 |
| 6 | | |
| 0,5 | / | 5 |
| 110 | | |
| PA - UL 94 V0 | | |
| M3 | | |
| 0,6 x 3,5 | | |

| | | |
|-----|----|----------------------|
| V | A | mm ² /AWG |
| 750 | 24 | 0,5 ÷ 2,5 |
| 300 | 16 | 30 ÷ 12 |

| |
|-------------------------------------|
| min 2 - max 12 |
| VE / on demand GR GR1 NE AR BL RO G |
| D/A1 |



MRT15..DP

Single block - Blocco unico
Monoblocc - Einzelblock

Poles - Poli - Póles - Polzahl 2/12



| |
|------------|
| 10 - 10,16 |
| 630 |
| 24 |

| | | |
|--------------------|----------------------|----------------------|
| 0,2 ÷ 4 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 | 0,2 ÷ 2,5 30 ÷ 12 |
| 6 | | |
| 0,5 | / | 5 |
| 110 | | |
| PA - UL 94 V0 | | |
| M3 | | |
| 0,6 x 3,5 | | |

| | | |
|-----|----|----------------------|
| V | A | mm ² /AWG |
| 750 | 24 | 0,5 ÷ 2,5 |
| 300 | 16 | 30 ÷ 12 |

| |
|-------------------------------------|
| min 2 - max 12 |
| VE / on demand GR GR1 NE AR BL RO G |
| D/A1 |

