



- fitted with**
- work equipment**
- connected load**
- power consumption**
- luminous flux**
- luminous efficacy**
- illuminance efficiency factor**
- light colour**
- color rendering index (CRI)**
- consistent white light of**
- glare-free**
- class of protection**
- technology**
- luminaire body**
- lamp cover**
- tubular sections**
- balance of articulation joints**
- weight (net)**
- mains lead**
- fastening**
- special features**

- LED
- Energy efficiency category A+
- electronic plug-in transformer
- 100-240 V; 50/60 Hz
- approx. 7 W
- approx. 530 lm
- approx. 75 lm/W
- 102 lx/W
- warm white, approx. 3000 K
- > 90 (R9>50)
- < 4 SDCM
- plastic reflector
- II with plug-in power supply; III without plug-in power supply
- continuously dimmable
- aluminium, painted, black
- screen, clear
- tubular aluminium section, painted, black
- friction
- approx. 1.0 kg
- approx. 3 m; mains plug
- US-ConnectionStandard
- adaptor (accessory), table base (accessory), table clamp (accessory)
- automatic switchoff adjustable, push button in luminaire head, behaviour at net recovery adjustable




* Separate ENEC certification for luminaire and power supply



CEE 7/XVI

illuminance

distance: 50 cm
Em: 750 lx
Emax: 1127 lx
Emin: 414 lx



luminous intensity

