



fitted with

work equipment
connected load
power consumption
power factor
luminous flux
luminous efficacy
light distribution
direct ratio
light colour
color rendering index (CRI)

glare-free
luminance
unified glare rating
technology
usage
luminaire body
lamp cover
tubular section
luminaire base
weight (net)
mains lead

fastening
decorative contrast side parts
special features

LED
 light colour daylight white, 3000-6500 K
 Energy efficiency category A+
 LED
 light colour neutral white, 4000 K
 Energy efficiency category A+
 electronic ballast
 220-240V; 50/60Hz
 approx. 94 W
 approx. 0,966
 approx. 11500 lm
 approx. 122 lm/W
 direct/indirect
 approx. 17 %
 adjustable white
 > 80
 conical prismatic screen
 < 2800 cd/m²
 < 16
 controlled depending on presence and daylight
 multi-function switch
 steel/plastic, painted, white
 polycarbonate, clear
 steel tube, painted, tubular section upright, white
 C-form flat
 approx. 18.5 kg
 approx. 3,0 m; mains plug
 CEE 7/II
 floor standing base
 flint grey
 luminaire head detachable, integrated light- and
 presence-detecting sensor PULSE, integrated light
 management for biodynamic light PULSE VTL, light forming,
 retrofit with EnOcean wireless module PULSE-TALK



PULSE VTL



CEE 7/II

luminous intensity

