

USEPARTOUT SUPERFLAT / USEPARTOUT SUPERFLAT / USEPARTOUT SUPERFLAT / 4000-EL83-GR

## Product Info




|                         |  |
|-------------------------|--|
| <b>Item code</b>        | USEPARTOUT SUPERFLAT / 4000-EL83-GR                              |
| <b>Category</b>         | Step light   |
| <b>Environments</b>     | residential lighting, hallway, wellness, urban landscape         |
| <b>Mounting type</b>    | surface  |
| <b>Body</b>             | Polycarbonate housing. Snap-in latches built into the structure. |
| <b>Painting</b>         | Injection molded body in colored polymer blend.                  |
| <b>Standard Colour</b>  | GR   graphite satin finish                                       |
| <b>Color on request</b> | CO   Corten, DN   embossed white                                 |



## Dimensions

|                                 |     |
|---------------------------------|-----|
| <b>Total device height (mm)</b> | 150 |
| <b>Total device width (mm)</b>  | 27  |
| <b>Total device length (mm)</b> | 340 |
| <b>Weight (kg)</b>              | 1   |




## Optical System

|                   |              |
|-------------------|--------------|
| <b>Beam</b>       | asymmetrical |
| <b>Emission</b>   | direct       |
| <b>Adjustable</b> | No           |



## Photometrics



Total return LOR (%)100%

## Sources

|                           |              |
|---------------------------|--------------|
| <b>MacAdam</b>            | Step 3       |
| <b>Output Flux</b>        | 380 lm       |
| <b>Source type</b>        | LED          |
| <b>System power</b>       | 9W           |
| <b>Temperature Colour</b> | 3000K CRI>80 |

## Electrical

|                              |   |
|------------------------------|---|
| <b>Ballast type</b>          | DALI  |
| <b>Frequency</b>             | 50-60Hz   |
| <b>Lifetime</b>              | 70.000h L80B10 (Ta=25°C)  |
| <b>Line input</b>            | Use only (EN 60598-1) a three core H07RN-F rubber cable with diameter between 7,5 and 12mm. |
| <b>Mounting ballast type</b> | Integral  |
| <b>Voltage</b>               | 220-240V  |
| <b>Separate ignition</b>     | No  |
| <b>Emergency 1E</b>          | No  |
| <b>Emergency 3E</b>          | No  |