

USEPARTOUT SUPERFLAT / USEPARTOUT SUPERFLAT / USEPARTOUT SUPERFLAT / 4000-EL84-AL

## Product Info




<b>Item code</b>	USEPARTOUT SUPERFLAT / 4000-EL84-AL
<b>Category</b>	Step light
<b>Environments</b>	residential lighting, hallway, wellness, urban landscape
<b>Mounting type</b>	surface
<b>Body</b>	Polycarbonate housing. Snap-in latches built into the structure.
<b>Painting</b>	Injection molded body in colored polymer blend.
<b>Standard Colour</b>	AL   aluminium grey
<b>Color on request</b>	CO   Corten, DN   embossed white



## Dimensions

<b>Total device height (mm)</b>	150
<b>Total device width (mm)</b>	27
<b>Total device length (mm)</b>	340
<b>Weight (kg)</b>	1




## Optical System

<b>Beam</b>	asymmetrical
<b>Emission</b>	direct
<b>Adjustable</b>	No



## Photometrics



Total return LOR (%)100%

## Sources

<b>MacAdam</b>	Step 3
<b>Output Flux</b>	475 lm
<b>Source type</b>	LED
<b>System power</b>	9W
<b>Temperature Colour</b>	4000K CRI>80

## Electrical

<b>Ballast type</b>	DALI
<b>Frequency</b>	50-60Hz
<b>Lifetime</b>	70.000h L80B10 (Ta=25°C)
<b>Line input</b>	Use only (EN 60598-1) a three core H07RN-F rubber cable with diameter between 7,5 and 12mm.
<b>Mounting ballast type</b>	Integral
<b>Voltage</b>	220-240V
<b>Separate ignition</b>	No
<b>Emergency 1E</b>	No
<b>Emergency 3E</b>	No