

USEPARTOUT SUPERFLAT / USEPARTOUT SUPERFLAT / USEPARTOUT SUPERFLAT / 4000-EL84-GR

Product Info




Item code	USEPARTOUT SUPERFLAT / 4000-EL84-GR
Category	Step light
Environments	residential lighting, hallway, wellness, urban landscape
Mounting type	surface
Body	Polycarbonate housing. Snap-in latches built into the structure.
Painting	Injection molded body in colored polymer blend.
Standard Colour	GR graphite satin finish
Color on request	CO Corten, DN embossed white



Dimensions

Total device height (mm)	150
Total device width (mm)	27
Total device length (mm)	340
Weight (kg)	1




Optical System

Beam	asymmetrical
Emission	direct
Adjustable	No



Photometrics



Total return LOR (%)100%

Sources

MacAdam	Step 3
Output Flux	425 lm
Source type	LED
System power	9W
Temperature Colour	4000K CRI>80

Electrical

Ballast type	DALI
Frequency	50-60Hz
Lifetime	70.000h L80B10 (Ta=25°C)
Line input	Use only (EN 60598-1) a three core H07RN-F rubber cable with diameter between 7,5 and 12mm.
Mounting ballast type	Integral
Voltage	220-240V
Separate ignition	No
Emergency 1E	No
Emergency 3E	No