


FL ROUND 777 RE



WH-RAL9016 / White RAL9016 / Textured

Scan the QR-code for the latest information

Recessed round LED luminaire for indoor, comprising:

→ Housing made from sheet steel and die-cast aluminium, powder-coated

The luminaire is available with different light engines:

- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Opal white diffuser for optimum light distribution and excellent uniformity (OP)
- LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the diffuser
- Direct light distribution
- Glare prevention in accordance with DIN EN 12464-1 (for designs with micro prism)
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Built-in driver




Ergosign offices - Saarbrücken - Germany



FL ROUND 333 / 555 / 777 PL



FL ROUND 333 / 555 AB - 777 SM



 443 mm  max 12 kg

FL ROUND 777 RE

FL ROUND 777 RE MP

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

69	I	-	-	80	4000	10500	7890	<input type="checkbox"/>	8777561763410	✓
69	I	-	-	80	3000	10200	7650	<input type="checkbox"/>	8777561763310	✓
45	I	-	✓	80	4000	7300	5420	<input type="checkbox"/>	8777561483410	✓
45	I	-	✓	80	3000	7100	5260	<input type="checkbox"/>	8777561483310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

69	I	-	-	80	4000	10500	7890	<input type="checkbox"/>	8777561766410	✓
69	I	-	-	80	3000	10200	7650	<input type="checkbox"/>	8777561766310	✓
45	I	-	✓	80	4000	7300	5420	<input type="checkbox"/>	8777561486410	✓
45	I	-	✓	80	3000	7100	5260	<input type="checkbox"/>	8777561486310	✓



FL ROUND 777 RE OP

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
-----------------------	-------	------	----------------	-----	--------	-------------------------------	-----------------------------	-----------------	-------------	------

Power LED 220-240 V 50/60 Hz

69	I	-	-	80	4000	10500	8370	<input type="checkbox"/>	8777591763410	✓
69	I	-	-	80	3000	10200	8120	<input type="checkbox"/>	8777591763310	✓
45	I	-	-	80	4000	7300	5790	<input type="checkbox"/>	8777591483410	✓
45	I	-	-	80	3000	7100	5620	<input type="checkbox"/>	8777591483310	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

69	I	-	-	80	4000	10500	8370	<input type="checkbox"/>	8777591766410	✓
69	I	-	-	80	3000	10200	8120	<input type="checkbox"/>	8777591766310	✓
45	I	-	-	80	4000	7300	5790	<input type="checkbox"/>	8777591486410	✓
45	I	-	-	80	3000	7100	5620	<input type="checkbox"/>	8777591486310	✓




Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
FL ROUND 777 RE			
External Casambi module	<input checked="" type="checkbox"/>	3122585	✓
Single wireless wall switch	<input type="checkbox"/>	3122586	✓
Double wireless wall switch	<input type="checkbox"/>	3122587	✓



3122585



3122586



3122587