



light source

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- illuminance efficiency factor**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**
- glare control**
- class of protection**
- technology**
- luminaire body**
- lamp cover**
- tubular sections**
- balance of articulation joints**
- weight (net)**
- mains lead**

Fastening

special features

LED


- Energy efficiency category A/A+/A++
- electronic plug-in transformer
- 100-240 V; 50/60 Hz
- approx. 7 W
- approx. 550 lm
- approx. 78 lm/W
- 111 lx/W
- neutral white, approx. 4000 K
- >= 90 (R9>50)
- 3 SDCM
- plastic reflector
- II with plug-in power supply; III without plug-in power supply
- continuously dimmable
- aluminium, painted, black
- screen, clear
- tubular aluminium section, painted, black
- friction
- approx. 1.0 kg
- approx. 3 m; mains plug
- CEE 7/XVI
- adaptor (accessory), table base (accessory), table clamp (accessory)
- automatic switchoff adjustable, push button in luminaire head, behaviour at net recovery adjustable



CEE 7/XVI

illuminance

distance: 50 cm
Em: 775 lx
Emax: 1166 lx
Emin: 430 lx



luminous intensity

