


# FLEXILED SM




Scan the QR-code for the latest information


WH-RAL9016 / White RAL9016 / Textured

Indoor surface mounted luminaire, comprising:


- Housing made of form-stable 1.0 mm sheet steel
  - Impact-resistant, impression-resistant powder coating
- The luminaire is available with different light engines:
- Black reflector ensures maximum efficiency and high visual comfort
  - Wallwasher with asymmetrical light distribution ensures optimum panel illumination
  - Opal PMMA diffuser for optimal light distribution and uniformity
  - Microprism for glare-free and barrier-free light at the workplace
  - Suitable for office applications in accordance with EN 12464-1
  - UGR < 19 for all luminositities
  - Luminaire efficiency of up to 175 lm/W
  - Reliable and low-maintenance 50,000h L80B10
  - Colour tolerance according to MacAdam  $\leq 3$  SDCM
  - 2 power levels adjustable
  - Special colour versions available. Consult factory




FLEXILED SM  
LV



FLEXILED SM  
LV



FLEXILED SM



FLEXILED SM

## FLEXILED SM LV BLACK

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	✓	80	4000	3750	3230	□	1500	<b>3122037</b>	✓
32	I	-	✓	80	4000	5500	4780	□	1500	<b>3122037</b>	✓
17	I	-	✓	80	4000	3000	2590	□	1200	<b>3122036</b>	✓
26	I	-	✓	80	4000	4400	3830	□	1200	<b>3122036</b>	✓
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>											
21	I	-	✓	80	4000	3750	3230	□	1500	<b>3122039</b>	✓
32	I	-	✓	80	4000	5500	4780	□	1500	<b>3122039</b>	✓
17	I	-	✓	80	4000	3000	2590	□	1200	<b>3122038</b>	✓
26	I	-	✓	80	4000	4400	3830	□	1200	<b>3122038</b>	✓



## FLEXILED SM LV ASYM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	-	80	4000	3750	3610	□	1500	<b>3122045</b>	✓
32	I	-	-	80	4000	5500	5340	□	1500	<b>3122045</b>	✓
17	I	-	-	80	4000	3000	2890	□	1200	<b>3122044</b>	✓
26	I	-	-	80	4000	4400	4270	□	1200	<b>3122044</b>	✓
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>											
21	I	-	-	80	4000	3750	3610	□	1500	<b>3122047</b>	✓
32	I	-	-	80	4000	5500	5340	□	1500	<b>3122047</b>	✓
17	I	-	-	80	4000	3000	2890	□	1200	<b>3122046</b>	✓
26	I	-	-	80	4000	4400	4270	□	1200	<b>3122046</b>	✓



## FLEXILED SM MICROPRISM

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
14	I	-	-	80	4000	2560	2060	□	1500	<b>3122553</b>	✓
24	I	-	-	80	4000	4200	3390	□	1500	<b>3122553</b>	✓
12	I	-	-	80	4000	2130	1670	□	1200	<b>3122552</b>	✓
20	I	-	-	80	4000	3360	2630	□	1200	<b>3122552</b>	✓
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>											
14	I	-	-	80	4000	2560	2060	□	1500	<b>3122555</b>	✓
24	I	-	-	80	4000	4200	3390	□	1500	<b>3122555</b>	✓
12	I	-	-	80	4000	2130	1670	□	1200	<b>3122554</b>	✓
20	I	-	-	80	4000	3360	2630	□	1200	<b>3122554</b>	✓



## FLEXILED SM OPAL


IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
14	I	-	-	80	4000	2560	2170	□	1500	<b>3122561</b>	✓
24	I	-	-	80	4000	4200	3560	□	1500	<b>3122561</b>	✓
12	I	-	-	80	4000	2130	1770	□	1200	<b>3122560</b>	✓
20	I	-	-	80	4000	3360	2790	□	1200	<b>3122560</b>	✓
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>											
14	I	-	-	80	4000	2560	2170	□	1500	<b>3122563</b>	✓
24	I	-	-	80	4000	4200	3560	□	1500	<b>3122563</b>	✓
12	I	-	-	80	4000	2130	1770	□	1200	<b>3122562</b>	✓
20	I	-	-	80	4000	3360	2790	□	1200	<b>3122562</b>	✓




## Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
<b>FLEXILED SM</b>			
Mounting template	■	<b>3122577</b>	✓
Casambi module for installation		<b>3122584</b>	✓
Single wireless wall switch	■	<b>3122586</b>	✓
Double wireless wall switch	■	<b>3122587</b>	✓




3122586



3122587

# FLEXILED IL




Scan the QR-code for the latest information


WH-RAL9016 / White RAL9016 / Textured

Inlayed for indoor use consisting of:


- Housing made of form-stable 1.0 mm sheet steel
- Impact-resistant, impression-resistant powder coating
- Black, white or metallised reflector ensure maximum efficiency and high visual comfort
- Suitable for office applications in accordance with EN 12464-1
- UGR < 19 for all luminosities
- Luminaire efficiency of up to 175 lm/W
- Reliable and low-maintenance 50,000h L80B10
- Colour tolerance according to MacAdam  $\leq 3$  SDCM
- 2 power levels adjustable
- Configurable via LIGHT-PERFORMER®
- Special colour versions available. Consult factory




FLEXILED IL LV



FLEXILED IL LV



FLEXILED IL LV



FLEXILED IL LV



CONFIGURATOR LIGHT-PERFORMER®  
www.light-performer.com

## FLEXILED IL LV BLACK

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	✓	80	4000	3750	3230	□	1500	<b>3120848</b>	✓
32	I	-	✓	80	4000	5500	4780	□	1500	<b>3120848</b>	✓
21	I	-	✓	80	4000	3750	3230	□	1495	<b>3122382</b>	✓
32	I	-	✓	80	4000	5500	4780	□	1495	<b>3122382</b>	✓
17	I	-	✓	80	4000	3000	2590	□	1200	<b>3120847</b>	✓
26	I	-	✓	80	4000	4400	3830	□	1200	<b>3120847</b>	✓
17	I	-	✓	80	4000	3000	2590	□	1195	<b>3122381</b>	✓
26	I	-	✓	80	4000	4400	3830	□	1195	<b>3122381</b>	✓



## FLEXILED IL LV SILVER

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	✓	80	4000	3750	3610	□	1500	<b>3120852</b>	✓
32	I	-	✓	80	4000	5500	5340	□	1500	<b>3120852</b>	✓
21	I	-	✓	80	4000	3750	3610	□	1495	<b>3122439</b>	✓
32	I	-	✓	80	4000	5500	5340	□	1495	<b>3122439</b>	✓
17	I	-	✓	80	4000	3000	2890	□	1200	<b>3120851</b>	✓
26	I	-	✓	80	4000	4400	4270	□	1200	<b>3120851</b>	✓
17	I	-	✓	80	4000	3000	2890	□	1195	<b>3122438</b>	✓
26	I	-	✓	80	4000	4400	4270	□	1195	<b>3122438</b>	✓



## FLEXILED IL LV WHITE

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	-	80	4000	3750	3560	□	1500	<b>3120850</b>	✓
32	I	-	-	80	4000	5500	5260	□	1500	<b>3120850</b>	✓
21	I	-	-	80	4000	3750	3560	□	1495	<b>3122437</b>	✓
32	I	-	-	80	4000	5500	5260	□	1495	<b>3122437</b>	✓
17	I	-	-	80	4000	3000	2840	□	1200	<b>3120849</b>	✓
26	I	-	-	80	4000	4400	4210	□	1200	<b>3120849</b>	✓
17	I	-	-	80	4000	3000	2840	□	1195	<b>3122383</b>	✓
26	I	-	-	80	4000	4400	4210	□	1195	<b>3122383</b>	✓




## Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
<b>FLEXILED IL</b>			
External Casambi module	■	<b>3122585</b>	✓
Single wireless wall switch	□	<b>3122586</b>	✓
Double wireless wall switch	□	<b>3122587</b>	✓



3122585



3122586



3122587

# FLEXILED RE




Scan the QR-code for the latest information


WH-RAL9016 / White RAL9016 / Textured

Recessed lights, comprising:

- Housing made of form-stable 1.0 mm sheet steel
- Impact-resistant, impression-resistant powder coating
- Black, white or metallised reflector ensure maximum efficiency and high visual comfort
- Suitable for office applications in accordance with EN 12464-1
- UGR < 19 for all luminosities
- Luminaire efficiency of up to 175 lm/W
- Reliable and low-maintenance 50,000h L80B10
- Colour tolerance according to MacAdam  $\leq 3$  SDCM
- 2 power levels adjustable
- Incl. pre-assembled installation spring
- Special colour versions available. Consult factory



FLEXILED RE LV



FLEXILED RE LV



CONFIGURATOR LIGHT-PERFORMER®  
[www.light-performer.com](http://www.light-performer.com)

## FLEXILED RE LV BLACK

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	✓	80	4000	3750	3230	□	1500	<b>3122228</b>	✓
32	I	-	✓	80	4000	5500	4780	□	1500	<b>3122228</b>	✓
17	I	-	✓	80	4000	3000	2590	□	1200	<b>3122225</b>	✓
26	I	-	✓	80	4000	4400	3830	□	1200	<b>3122225</b>	✓



## FLEXILED RE LV SILVER

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	✓	80	4000	3750	3610	□	1500	<b>3122229</b>	✓
32	I	-	✓	80	4000	5500	5340	□	1500	<b>3122229</b>	✓
17	I	-	✓	80	4000	3000	2890	□	1200	<b>3122226</b>	✓
26	I	-	✓	80	4000	4400	4270	□	1200	<b>3122226</b>	✓



## FLEXILED RE LV WHITE

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	LENGTH (mm)	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
21	I	-	-	80	4000	3750	3560	□	1500	<b>3122230</b>	✓
32	I	-	-	80	4000	5500	5260	□	1500	<b>3122230</b>	✓
17	I	-	-	80	4000	3000	2840	□	1200	<b>3122227</b>	✓
26	I	-	-	80	4000	4400	4210	□	1200	<b>3122227</b>	✓




Office

## Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
<b>FLEXILED RE</b>			
External Casambi module	■	<b>3122585</b>	✓
Single wireless wall switch	□	<b>3122586</b>	✓
Double wireless wall switch	□	<b>3122587</b>	✓



3122585



3122586



3122587