

# GUELL 2



GR-94 / Metallic grey / Textured





Scan the QR-code for the latest information



Church of St. George in Braida - Verona - Italy

LED floodlight for indoor and outdoor, comprising:





- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- High asymmetrical distributions low-glare optic options available (A50/W versions)
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Dimmable ballast available. Consult factory
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- For integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM) consult factory
- Design by GIORGIO LODI



GUELL 2

GUELL 2  
C/I

Identifying and classifying our optics



## GUELL 2 S/W

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	URCA
<b>Power LED 220-240 V 50/60 Hz</b>											
149	I	-	80	4000	S/W	-	25350	20335	■	<b>3112391</b>	✓
149	I	-	80	3000	S/W	-	24089	19324	■	<b>3112388</b>	✓
103	I	-	80	4000	S/W	-	16198	13233	■	<b>3115110</b>	✓
103	I	-	80	3000	S/W	-	15320	12830	■	<b>3115111</b>	✓
74	I	-	80	4000	S/W	-	12148	10463	■	<b>3115115</b>	✓
74	I	-	80	3000	S/W	-	11196	10150	■	<b>3115116</b>	✓
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>											
149	I	-	80	4000	S/W	-	25350	20343	■	<b>3116909</b>	✓
149	I	-	80	3000	S/W	-	24089	19331	■	<b>3116910</b>	✓
103	I	-	80	4000	S/W	-	16198	13233	■	<b>3115113</b>	✓
103	I	-	80	3000	S/W	-	15320	12830	■	<b>3115114</b>	✓
74	I	-	80	4000	S/W	-	12148	10463	■	<b>3115118</b>	✓



## GUELL 2 A/W

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	URCA
<b>Power LED 220-240 V 50/60 Hz</b>											
149	I	-	80	4000	A40/W	-	25350	20323	■	<b>3112390</b>	✓
149	I	-	80	3000	A40/W	-	24089	19312	■	<b>3112387</b>	✓
103	I	-	80	4000	A40/W	-	16198	13006	■	<b>3115119</b>	✓
103	I	-	80	3000	A40/W	-	15320	12619	■	<b>3115120</b>	✓
74	I	-	80	4000	A40/W	-	12148	10030	■	<b>3115125</b>	✓
74	I	-	80	3000	A40/W	-	11196	9605	■	<b>3115126</b>	✓
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>											
149	I	-	80	4000	A40/W	-	25350	20329	■	<b>3116911</b>	✓
149	I	-	80	3000	A40/W	-	24089	19318	■	<b>3116912</b>	✓
103	I	-	80	4000	A40/W	-	16198	13006	■	<b>3115122</b>	✓
103	I	-	80	3000	A40/W	-	15320	12619	■	<b>3115123</b>	✓
74	I	-	80	4000	A40/W	-	12148	10030	■	<b>3115128</b>	✓
74	I	-	80	3000	A40/W	-	11196	9605	■	<b>3115129</b>	✓



## GUELL 2 A50/W

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
<b>Power LED 220-240 V 50/60 Hz</b>											
80	I	-	80	4000	A50/W	-	12085	10032	■	<b>3115103</b>	✓
80	I	-	80	3000	A50/W	-	10182	9396	■	<b>3115102</b>	✓



## GUELL 2 C/I

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	IP66 - IK07 - 650 °C
<b>Power LED 220-240 V 50/60 Hz</b>											
101	I	-	80	4000	C/I	-	14552	11930	■	<b>3115108</b>	✓
101	I	-	80	3000	C/I	-	14118	11471	■	<b>3115107</b>	✓
72	I	-	80	4000	C/I	-	11116	9470	■	<b>3115105</b>	✓
72	I	-	80	3000	C/I	-	10784	9105	■	<b>3115104</b>	✓



## Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
<b>GUELL 2</b>			
Protective grid GUELL 2		<b>14173502</b>	✓
Connection box IP 66		<b>14174220</b>	✓
Wall support 500 mm/19.69" GUELL 1/2	■	<b>14173394</b>	✓
Wall support 1000 mm/39.37" GUELL 1/2	■	<b>14173494</b>	✓
Single pole top support GUELL 2	■	<b>14174094</b>	✓
Double pole top support GUELL 2	■	<b>14174194</b>	✓
Reinforcing bracket GUELL 2 in painted steel. Used to fasten the floodlight with a single screw in the centre of the bracket	■	<b>14460594</b>	✓
<b>GUELL 2 S/W</b>			
Louvre GUELL 2 Symmetrical		<b>14173720</b>	✓
<b>GUELL 2 S/W - GUELL 2 A/W</b>			
Soft glass GUELL 2	■	<b>14173994</b>	✓
<b>GUELL 2 A/W</b>			
Cover GUELL 2 Asymmetrical	■	<b>14173694</b>	✓
Louvre GUELL 2 Asymmetrical		<b>14173820</b>	✓
<b>GUELL 2 C/I</b>			
GUELL 2/C frosted glass		<b>14476794</b>	✓





Timing sport center - Brescia - Italy