

114130000-00805671



light source

- work equipment**
- connected load**
- Power consumption**
- standby**
- power factor**
- luminous flux**
- luminous efficacy**
- light distribution**
- direct ratio**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**
- glare control**
- luminance (L65)**
- unified glare rating (4H 8H)**
- System of protection**
- technology**
- operation**
- luminaire body**
- lamp cover**
- Dimming Range**
- weight (net)**
- mains lead**
- Fastening**
- Configuration**
- dimension**
- special features**

LED

Energy efficiency category A/A+/A++
 adjustable electronic ballast; digital DALI
 220-240 V; 50/60 Hz
 approx. 17 W
 approx. 0,20 W
 approx. 0,970
 approx. 2350 lm
 approx. 138 lm/W
 direct/indirect
 approx. 40 %
 neutral white, approx. 4000 K
 >= 80
 3 SDCM
 conical prismatic screen
 <= 2700 cd/m²
 <= 16
 IP40
 DALI, continuously dimmable
 external
 sectional aluminium, white
 acrylic clear
 1-100%
 approx. 3.3 kg
 approx. 2,0 m; with free stranded wires
 steel cable 0.3 - 0.7 m
 Single Luminaire
 L=854mm
 DALI Load 1x, TouchDIM - dimming via standard switch,
 Flicker-free, Suitable as emergency lighting



luminous intensity

