


## MASK+ B




<b>Part number</b>	3100768
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	24 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Symmetric extra wide reflector
<b>Lightsource lumen output:</b>	3104 lm
<b>Luminaire lumen output:</b>	1770 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°



### Description

- Indoor and outdoor wall-mount fixture, including:
- ISO 9227 painted die-cast aluminium housing
  - Glass diffuser, internally painted for homogeneous diffused light
  - Silicone gasket
  - M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
  - Double-emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
  - EM/1P are maintained emergency versions (MASK+)
  - Emergency - 1 hour
  - Versions with dimmable ballast available DALI. Consult Factory
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

