

MASK+ M




Part number	3100766
Lampholder:	LED
Light Source:	LED
Wattage:	12,5 W
Finish:	WH-87 / White / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric extra wide reflector
Lightsource lumen output:	1668 lm
Luminaire lumen output:	971 lm
L:	L70
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°
ULR:	0%



Description

- Indoor and outdoor wall-mount fixture, including:
- ISO 9227 painted die-cast aluminium housing
 - Glass diffuser, internally painted for homogeneous diffused light
 - Silicone gasket
 - M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
 - Double-emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
 - EM/1P are maintained emergency versions (MASK+)
 - Emergency - 1 hour
 - Versions with dimmable ballast available DALI. Consult Factory
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

