


MASK+ MINI B




Part number	3101604
Lampholder:	LED
Light Source:	LED
Wattage:	16 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric extra wide reflector
Lightsource lumen output:	1450 lm
Luminaire lumen output:	627 lm
L:	L70
B:	B10
Lifetime:	54000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°



Description

- Indoor and outdoor wall-mount fixture, including:
- ISO 9227 painted die-cast aluminium housing
 - Glass diffuser, internally painted for homogeneous diffused light
 - Mains voltage 220-240V 50/60Hz LED module protected against surges up to 500 V
 - Silicone gasket
 - M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
 - Double-emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
 - DETEK versions available on request
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

