

**MOON** is the new device for **wall** or **ceiling installations**. The **minimal design and IP65 protection** rating make it suitable for general lighting in any context, both **indoor** and **outdoor**, such as **stairs, corridors, passageways, parking lots** and wherever sober lighting is needed.

#### ☑ Features

- Direct emission
- IP 65
- IK10
- -25° → +40°/45°
- 750°

#### 💡 Led

- 3000K/4000K
- >100lm/W
- CRI >80
- Eye safety: RGO
- Mac Adams 3
- L80/B10 >50.000h

#### 🕒 Specifications

- SMD LED technology
- Built-in driver
- Impact resistant polycarbonate diffuser

#### 📦 Body

- Polycarbonate

#### 🎨 Colors

- White RAL 9003 - code B
- Black RAL 9005 - code C8

#### 🌟 Certifications

- CE Conformity
- Energy efficiency E
- 5 years warranty

#### 📦 On request


- DALI - code D\*
- Emergency 1 hr - code EM\*
- Emergency 3 hrs - code EM3H\*

*\* Where available*



# MOON SMALL

Impact resistant polycarbonate diffuser.




IP 65 IK10

Cod. 4000K	Led	lm	Ømm
5IPO13K4S65	13W	1158	200

Cod. 3000K	Led	lm	Ømm
5IPO13K3S65	13W	1055	200

# MOON MEDIUM

Impact resistant polycarbonate diffuser.




IP 65 IK10

Cod. 4000K	Led	lm	Ømm
5IPO18K4M65	18W	2014	275
5IPO25K4M65	25W	2515	275

Cod. 3000K	Led	lm	Ømm
5IPO18K3M65	18W	1921	275
5IPO25K3M65	25W	2340	275

## MOON LARGE

Impact resistant polycarbonate diffuser.



IP 65 IK10


Cod. 4000K	Led	lm	Ømm
5IPO27K4L65	27W	3173	350

Cod. 3000K	Led	lm	Ømm
5IPO27K3L65	27W	3005	350

## MOON INTELLIGENT

Impact resistant polycarbonate diffuser.

Built-in presence sensor.



IP 65 IK10

Cod. 4000K	Led	lm	Ømm
5IPO18K4M65I	18W	2014	275
5IPO25K4M65I	25W	2515	275
5IPO27K4L65I	27W	3173	350

Cod. 3000K	Led	lm	Ømm
5IPO18K3M65I	18W	1921	275
5IPO25K3M65I	25W	2340	275
5IPO27K3L65I	27W	3005	350