


ORION POST 600




Part number	3106293
Lampholder:	LED
Light Source:	LED
Wattage:	5,5 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric extra wide reflector
Lightsource lumen output:	742 lm
Luminaire lumen output:	409 lm
L:	L70
B:	B10
Lifetime:	35000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°
ULR:	0%
IPEA* (Street Lighting):	B
IPEA* (Area Lighting):	B
IPEA* (Cycle/Pedestrian Lighting):	C
IPEA* (Green Areas):	C
IPEA* (Historical Areas):	A+
Luminous Intensity Class:	G*6



Description

- Landscaping LED bollard, comprising:
- Die-cast aluminium housing, powder-polyester coated ISO 9227
 - Extra-clear, tempered, flat glass diffuser, screen-printed inside
 - Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
 - Aluminium reflector
 - Anti-ageing silicone gasket
 - Painted extruded aluminium pole (ORION POST 600)
 - Base plate included
 - External electrical connection with IP-rated QUICK connector, complete with cable
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

