


QUASAR 10



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- BK-81 / Black / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Secured diffuser in printed transparent flat glass
- Foam polymer sealing gasket
- Stainless steel locking hardware
- Built-in driver
- Openable and maintainable luminaire (future-proof)



Private house - Andalusia - Spain



QUASAR 10 CEILING




QUASAR 10

QUASAR 10 1WB

IP44 - IK02


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
3.5	I	✓	80	4000	R	-	230	122	■	303355	✓
3.5	I	✓	80	3000	R	-	150	100	■	303354	✓
3.5	I	✓	80	4000	R	-	230	122	■	303357	✓
3.5	I	✓	80	3000	R	-	150	100	■	303356	✓
3.5	I	✓	80	3000	R	-	150	100	■	30335690104	✓
3.5	I	✓	80	4000	R	-	230	122	□	303451	✓
3.5	I	✓	80	3000	R	-	150	100	□	303450	✓



QUASAR 10 2WB

IP44 - IK02


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6	I	✓	80	4000	R	-	460	235	■	303361	✓
6	I	✓	80	3000	R	-	300	192	■	303360	✓
6	I	✓	80	4000	R	-	460	235	■	303363	✓
6	I	✓	80	3000	R	-	300	192	■	303362	✓
6	I	✓	80	3000	R	-	300	192	■	30336290102	✓
6	I	✓	80	4000	R	-	460	235	□	303453	✓
6	I	✓	80	3000	R	-	300	192	□	303452	✓



QUASAR 10 1NB+1WB

IP44 - IK02

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
6	I	✓	80	4000	R	-	460	141	■	303367	✓
6	I	✓	80	3000	R	-	300	113	■	303366	✓
6	I	✓	80	4000	R	-	460	141	■	303369	✓
6	I	✓	80	3000	R	-	300	113	■	303368	✓
6	I	✓	80	4000	R	-	460	141	□	303455	✓
6	I	✓	80	3000	R	-	300	113	□	303454	✓



QUASAR 10 4WB

IP44 - IK02

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
10.5	I	✓	80	4000	R	-	920	402	■	303349	✓
10.5	I	✓	80	3000	R	-	600	329	■	303348	✓
10.5	I	✓	80	4000	R	-	920	402	■	303351	✓
10.5	I	✓	80	3000	R	-	600	329	■	303350	✓
10.5	I	✓	80	4000	R	-	920	402	□	303449	✓
10.5	I	✓	80	3000	R	-	600	329	□	303448	✓

