



|  |                            |
|--|----------------------------|
| <b>Light source</b>                      | LED                        |
| <b>Work equipment</b>                    | Without                    |
| <b>Connected load</b>                    | 22 - 26 V; DC              |
| <b>Power consumption</b>                 | ca. 62,5 W                 |
| <b>Luminous flux</b>                     | approx. 4.700 lm           |
| <b>Luminous efficiency <sup>1)</sup></b> | approx. 74 lm/W            |
| <b>Light type/-color</b>                 | Cold white                 |
| <b>Colour temperatur</b>                 | approx. 5.000 K            |
| <b>Color rendering index</b>             | CRI ≥ 80                   |
| <b>Light distribution</b>                | Direct                     |
| <b>Direct ratio</b>                      | approx. 99 %               |
| <b>Beam angle</b>                        | 100°                       |
| <b>Chromaticity tolerance LED</b>        | < 4 SDCM                   |
| <b>Glare control</b>                     | Diffusor                   |
| <b>Luminance (L65)</b>                   | ≤ 14.000 cd/m <sup>2</sup> |
| <b>UGR class (4H 8H; EN 12464-1)</b>     | ≤ 25                       |
| <b>System of protection/Class</b>        | IP 67; III                 |
| <b>Technology</b>                        | Switchable                 |
| <b>Operation</b>                         | External                   |
| <b>Emergency lighting</b>                | none                       |
| <b>Housing</b>                           | Acrylic (PMMA), clear      |
| <b>Light source cover</b>                | Acrylic (PMMA)             |
| <b>Mains lead</b>                        | Built-in plug; ST16/2 BS   |
| <b>Fastening</b>                         | Pipe clamp (accessory)     |
| <b>Light output</b>                      | D=1436 mm                  |
| <b>Side part</b>                         | A with screwed cable gland |
| <b>Maximum ambient temperature</b>       | 40 °C                      |
| <b>EAN</b>                               | 4013330140236              |
| <b>Weight without/incl. packaging</b>    | ca. 3,9 kg; 4,5 kg         |
| <b>Dimensions (dimensional drawing)</b>  | A=1490 mm                  |
| <b>Packaging dimensions</b>              | ca. 1.700 mm; 90 mm; 90 mm |

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear.