



**light source**  
**work equipment**  
**connected load**  
**secondary tension**  
**power consumption**  
**sec. power consumption**  
**luminous flux**  
**luminous efficiency**  
**light type/-color**  
**colour temperatur**  
**color rendering index**  
**light distribution**  
**direct ratio**  
**chromaticity tolerance LED**  
**system of protection**  
**class of protection**  
**technology**  
**operation**  
**housing**  
**Light source cover**  
**arm**  
**balance of articulation joints**  
**weight (net)**  
**mains lead**  
**fastening**  
**lens, dimensions**  
**lens material**  
**lens, diopters**  
**special features**

LED  
electronic plug-in ballast  
100 - 240 V; AC; 50 Hz; 60 Hz  
24 V  
ca. 13 W  
ca. 11 W  
approx. 750 lm  
approx. 57 lm/W  
daylight  
approx. 6.500 K  
CRI ≥ 90; R9 ≥ 50  
direct  
approx. 100 %  
< 3 SDCM  
IP 20  
II with plug-in power supply, III without plug-in power supply  
multi-stage switchable; continuously dimmable;  
Touch DIM  
multi-function switch  
plastic; untreated; black  
Polyamide; milky  
tubular aluminium section; anodized; aluminium coloured anodised  
spring  
ca. 2,5 kg  
ca. 3,6 m; mains plug; CEE 7/XVI; BS 1363; NEMA 1-15P  
screw-down flange  
Ø 160 mm  
glass  
3,5  
antireflective glass lens; light characteristic can be adjusted with a three-way switch